Marvel Multi LED Flood Light

IMAGES						
Product	30watt Flood Light	45watt Flood Light	60watt Flood Light	80watt Flood Light	100watt Flood Light	150watt Flood Light
Lumens	2700 Lm	4050 Lm	5400 Lm	7200 Lm	9000 Lm	13500 Lm
Lumens Efficacy/watt	90 Lm/w	90 Lm/w	90 Lm/w	90 Lm/w	90 Lm/w	90 Lm/w
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
THD %	<10%	<10%	<10%	<10%	<10%	<10%
Total Power	30W	45W	60W	80W	100W	150watt
LED Power	1watt	1watt	1watt	1watt	1watt	1watt
No. of LED	27	39	54	68	84	123
LED Driver	Firefly Driver	Firefly Driver	Firefly Driver	Firefly Driver	Firefly Driver	Firefly Driver
Voltage	110-240v AC	110-240v AC	110-240v AC	110-240v AC	110-240v AC	110-240v AC
Over Voltage Protection	300volts	300volts	300volts	300volts	300volts	300volts
Under Voltage Protection	100volts	100volts	100volts	100volts	100volts	100volts
Short Circuit Protection	yes	yes	yes	yes	yes	yes
Open Circuit Protection	yes	yes	yes	yes	yes	yes
Surge Protection	yes	yes	yes	yes	yes	yes
Size	L250mm x W185mm x H130mm	L250mm x W185mm x H130mm	L315mm x W235mm x H150mm	L315mm x W235mm x H150mm	L340mm x W224mm x H105mm	L370mm x W290mm x H120mm
Type of LED	Cree / Citizen/ Sen Nikko	Cree / Citizen/ Sen Nikko	Cree / Citizen/ Sen Nikko	Cree / Citizen/ Sen Nikko	Cree / Citizen/ Sen Nikko	Cree / Citizen/ Sen Nikko
Beam Angle	60˚	60˚	60˚	60˚	120˚	120˚
CRI	>80	>80	>80	>80	>80	>80
Colour Temperature	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K
IP	IP67	IP67	IP67	IP67	IP67	IP67
Material	Aluminium Casting	Aluminium Casting	Aluminium Casting	Aluminium Casting	Aluminium Casting	Aluminium Casting
Diffuser	Toughened Glass	Toughened Glass	Toughened Glass	Toughened Glass	Toughened Glass	Toughened Glass
Net Weight						
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Working Temprature	(-20˚c To+70˚c)	(-20˚c To+70˚c)	(-20˚c To+70˚c)	(-20˚c To+70˚c)	(-20˚c To+70˚c)	(-20˚c To+70˚c)
Life Span	40000	40000	40000	40000	40000	40000
Warranty	2years	2years	2years	2years	2years	2years