Sleek Round & Square Panel Lights

IMAGES						
Product	9watt Sleek BLPL R	16watt Sleek BLPL R	9watt Sleek BLPL S	12watt Sleek BLPL S	16watt Sleek BLPL S	22watt Sleek BLPL S
Lumens	810 Lm	1440 Lm	810 Lm	1080 Lm	1440 Lm	1980 Lm
Lumens Efficacy/watt	90 Lm/w	90 Lm/w	90 Lm/w	90 Lm/w	90 Lm/w	90 Lm/w
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
THD %	<10%	<10%	<10%	<10%	<10%	<10%
Total Power	09W [R]	16W [R]	09W [S]	12W [S]	16W [S]	22W [S]
LED Power	0.2watt	0.2watt	0.2watt	0.2watt	0.2watt	0.2watt
No. of LED	35	70	35	55	70	95
LED Driver	3-9watt	16-24watt	3-9watt	8-15watt	16-24watt	16-24watt
Voltage	110-240v AC	110-240v AC	110-240v AC	110-240v AC	110-240v AC	110-240v AC
Over Voltage Protection	300volts	300volts	300volts	300volts	300volts	300volts
Under Voltage Protection	100volts	100volts	100volts	100volts	100volts	100volts
Short Circuit Protection	yes	yes	yes	yes	yes	yes
Open Circuit Protection	yes	yes	yes	yes	yes	yes
Surge Protection	yes	yes	yes	yes	yes	yes
Size	ø106mm x H 40mm (CD ø96mm)	ø178mm x H 30mm (CD ø163mm)	L 110mm x H 40mm (CD 100mm)	L 150mm x H 40mm (CD 134mm)	L 180mm x H 38mm (CD 164mm)	L 180mm x H 38mm (CD 164mm)
Type of LED	Cree LED / Sen Nikko or Equi-valent	Cree LED / Sen Nikko or Equi-valent	Cree LED / Sen Nikko or Equi-valent	Cree LED / Sen Nikko or Equi-valent	Cree LED / Sen Nikko or Equi-valent	Cree LED / Sen Nikko or Equi-valent
Beam Angle	120˚	120˚	120˚	120˚	120˚	120˚
CRI	>80	>80	>80	>80	>80	>80
Colour Temperature	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K
IP	IP40	IP40	IP40	IP40	IP40	IP40
Material	LSI 1132	LSI 1132	LSI 1132	LSI 1132	LSI 1132	LSI 1132
Diffuser	PC	PC	PC	PC	PC	PC
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Working Temprature	(-20˚c To +70˚c)	(-20˚c To +70˚c)	(-20˚c To +70˚c)	(-20˚c To +70˚c)	(-20˚c To +70˚c)	(-20˚c To +70˚c)
Life Span	40000	40000	40000	40000	40000	40000
Warranty	2years	2years	2years	2years	2years	2years